

Bakbricka m/hylsa vattentät



Bakbrickan med påsvetsad hylsa ger en vattentät bultgenomföring i membranet och PE-Skummet. Hylsan är inte genomgående, och därför kan vattnet inte följa med bulten igenom hylsan.

Lagerprogram:

Bakbricka m/hylsa vattentät M16*

Bakbricka m/hylsa vattentät M20*

*Andra dimensioner mot förfrågan

Teknisk information:

Kvalite efter önskemål. (1.4462, PCC)

Korrosionsskydd / Pc-Coat

Varmförzinkat enl. EN-ISO 1461 och epoxy pulverlacken blir utfört efter SS-EN 13438.

För detaljerad information om Pc-Coat, se produktdatablad för Pc-Coat.

Tillbehör:

Bultar för vatten och frostsäkring, frambricka och mutter.

Back plate /Water stop sleeve



The back plate with welded sleeve provides a waterproof bolt penetration in the membrane and PE foam. The sleeve is not continuous, and therefore the water cannot follow the bolt through the sleeve.

Stock program:

Back plate w / sleeve waterproof M16*

Back plate w / sleeve waterproof M20*

* Other dimensions on request

Technical information:

Quality as desired. (1.4462, PCC)

Corrosion protection / Pc-Coat

Hot-dip galvanized acc. EN-ISO 1461 and the epoxy powder coating are made according to SS-EN 13438.

For detailed information on Pc-Coat, see the Pc-Coat product data sheet.

Accessories:

Bolts for water and frost protection, front plate and nut.